

What is claimed is:

- 1 1. A method of producing a background image representing data comprising
- 2 the steps of:
 - 3 producing a first encoding of the data into a first binary array;
 - 4 producing a second encoding of the data into a second binary array;
 - 5 representing the first binary array as a first set of modules of a first size on
 - 6 nodes of a first lattice;
 - 7 representing the second binary array as a second set of modules of a
 - 8 second size, which is smaller than the first size on nodes of a second lattice;
 - 9 combining the first and second sets of modules; and
 - 10 printing the first and second sets of modules.

TOP SECRET - GAO/DOJ

- 1 2. The method claimed in claim 1, further including the step of:
 - 2 superimposing graphic material on the modules before printing.
- 1 3. The method claimed in claim 2, wherein the graphic material is a postal
- 2 indicia.
- 1 4. The method claimed in claim 1, wherein the modules on the first lattice
- 2 and the modules on the second lattice do not overlap.

1 5. A method for producing a composite image comprising the steps of:

2 producing a first image and a second image that embeds information in

3 the first image;

4 representing information contained in the second image by a two-

5 dimensional bar code;

6 filtering the two-dimensional bar code with a spreading algorithm that

7 scrambles the information represented by the two-dimensional bar code;

8 splitting the filter bar code into an equal first part and an equal second

9 part, wherein each first part and each second part will contain an upper portion

10 and a lower portion such that the lower portion of the first part and the upper

11 portion of the second part will be white or empty space;

12 applying a spreading algorithm to the first part and second part to further

13 hide the information in the first and second parts;

14 expanding the first and second parts over the entire image that is going to

15 be printed; and

16 printing the first and second parts over the first image to produce an image

17 containing hidden information.

1 6. The method claimed in claim 5, wherein the first image is a postal indicia.

1 7. The method claimed in claim 5, wherein the first and second images are
2 printed on a medium.

1 8. The method claimed in claim 5, wherein:
2 at each location in which information from the first parts is going to be
3 printed, the printed information will be a printed pixel of a specified dimension,
4 and
5 at each location in which information from the plurality of second parts is
6 going to be printed, the printed information will be a printed pixel of a specified
7 dimension that differs from the pixels printed in the first parts.

1 9. The method claimed in claim 5, wherein when the first and second images
2 are scanned and printed, the printed pixels of specified dimensions in the first
3 and second parts will become larger.

1 10. The method claimed in claim 9, wherein the change in size of the printed
2 pixels of specified dimensions in the first and second parts is detectable by the
3 unaided human eye.

1 11. The method claimed in claim 9, wherein the change in size of the printed
2 pixels of specified dimensions in the first and second parts is detectable by a
3 scanner.

1 12. The method claimed in claim 5, further including the steps of:
2 photocopying the first and second images; and
3 noticing a change in appearance of the second image.

1 13. The method claimed in claim 5, further including the steps of:
2 scanning the first and second images; and
3 noticing a change in appearance of the second image.

1 14. The method claimed in claim 5, wherein when the first and second images
2 are photocopied, the printed pixels of specified dimensions in the first and
3 second parts will become larger.

1 15. The method claimed in claim 14, wherein the change in size of the printed
2 pixels of specified dimensions in the first and second parts is detectable by the
3 unaided human eye.

1 16. The method claimed in claim 14, wherein the change in size of the printed
2 pixels of specified dimensions in the first and second parts is detectable by the
3 scanner.

1 17. The method claimed in claim 5, wherein the first image will not change in
2 appearance when the first image is scanned or photocopied.